

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 October 2001 (11.10.2001)

PCT

(10) International Publication Number
WO 01/74287 A1

(51) International Patent Classification⁷: **A61G 7/057**

(21) International Application Number: **PCT/GB01/01515**

(22) International Filing Date: **4 April 2001 (04.04.2001)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
0008399.8 **5 April 2000 (05.04.2000)** **GB**

(71) Applicant (for all designated States except US):
HUNTLEIGH TECHNOLOGY PLC [GB/GB];
310-312 Dallow Road, Luton, Bedfordshire LU1 1TD
(GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **CHAPMAN, Paul,**

William [GB/GB]; 12 Shakespeare Drive, Upper Caldecote, Beds SG18 9DD (GB). PERRY, Clive, Russell [GB/GB]; 99 Whitworth Way, Wilstead, Bedfordshire MK45 3EF (GB).


(74) Agent: **THAKER, Shalini; Group IPR Department, Huntleigh Technology PLC, 310-312 Dallow Road, Luton, Bedfordshire LU1 1TD (GB).**

(81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.**


(84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European**

[Continued on next page]

(54) Title: **INFLATABLE SUPPORT**



(57) Abstract: An alternating pad consisting of transverse inflatable cells (1 and 2) (not show) alternately inflated and deflated. An internal cell (5) is provided at the outermost edges of each transverse cell (1, 2). The internal cell (5) is constantly inflated at a higher pressure than the transverse cells (1, 2). The internal cell (5) is at a lower height than the cells (1, 2) and preferably of a chamfered shape to provide optimum pressure relief across the whole surface of the pad. The internal cell (5) provides stable patient exit, entry or transfer from a bed or seat.



WO 01/74287 A1



WO 01/74287 A1